

**Manufacturer:**

ÅngströmLap®

**Product Name:**

ÅngströmLap® - 4" 9um Silicon Carbide - PSA

**Manufacturer Part Number:**

SC9T403P100

[Learn More](#)

▶ [Click here for more details on the ÅngströmLap® - 4" 9um Silicon Carbide - PSA](#)

## PRODUCT SPECIFICATIONS:

### Description by Application

FO Type Name: SC9-CT

Color: Blue

### Tape Specifications

Total Thickness:  $92.0 \pm 2.0 \mu\text{m}$ Surface Roughness:  $2.6 \pm 0.6 \mu\text{m}$ 

### Abrasive Type

Particle Type: Silicon Carbide

Grit Size:  $9 \mu\text{m}$ 

### Base Film Type

Base Film Material: Poly-ethylene terephthalate

Base Film Thickness: 3 mil ( $75 \mu\text{m}$ )

### Process Parameters

Type: CT

**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are subject to change without notice.*



Manufacturer: ÅngströmLap®
Product Name: ÅngströmLap® - 4" 9um Silicon Carbide - PSA
Manufacturer Part Number: SC9T403P100

Click here for more details on the ÅngströmLap® - 4" 9um Silicon Carbide - PSA

PRODUCT SPECIFICATIONS:

Unit: Standard packaging of 100

Roll - Product that has already been slit down for samples or to product specifications requested by the customer. This specification standard covers tapes for various applications.

Disc - Product that has been slit down into rolls then die cut into circular discs to conform to customer specified sizes. This specification standard covers discs for various applications

Sheet - Product that has been slit down into rolls then sheet cut into rectangular sheets to conform to customer specified sizes. This specification standard covers sheets for various applications

Description:

Example: SC9-CT

Table with 4 columns: Abrasive Material, Average Grit Size, Process Type (C, T), and sub-categories: Silicon Carbide, 9 um, Mixing Ratio Type, Surface Shape Type

Lot Description:

Indicated by 10 digits number. Automatic numbering by enterprise resource planning system. Example: 0000012345

Product Specifications:

Mipox product standards are specified by the abrasive film Surface roughness and the total thickness diameter and length.

Storage Environment:

- Temperature: 10 to 50 centigrade
Humidity: 20 to 80%

Product Life: Mipox product life is guaranteed up to 5 years from the manufactured date

Recommended Usage: Usage amounts are conservative estimates and may vary based on individual conditions. Please contact Fiber Optic Center to optimize these usage numbers. Specifications subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.




**Manufacturer:**  
ÅngströmLap®

**Product Name:**  
ÅngströmLap® - 4" 9um Silicon Carbide - PSA

**Manufacturer Part Number:**  
SC9T403P100



▶ Click here for more details on the ÅngströmLap® - 4" 9um Silicon Carbide - PSA



**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are subject to change without notice.*