# SAFETY DATA SHEET



# 1. Identification

Covestro LLC 1 Covestro Circle Pittsburgh, PA 15205 USA

# TRANSPORTATION EMERGENCY

CALL CHEMTREC: INTERNATIONAL:

Raw material for coatings, inks, adhesives, sealants, or elastomers in

(800) 424-9300 (703) 527-3887

NON-TRANSPORTATION

Emergency Phone: Information Phone:

Cablelite 751-017 Blue

UV-Curable Mixture

industrial applications Do-It-Yourself Applications

50025108

Call Chemtrec (844) 646-0545

Product Name: Material Number: Chemical Family: Use:

**Restrictions on use:** 

#### 2. Hazards Identification

| GHS Classification<br>Skin irritation: | Category 2                                                    |
|----------------------------------------|---------------------------------------------------------------|
|                                        |                                                               |
| Eye irritation:                        | Category 2A                                                   |
| Skin sensitisation:                    | Category 1                                                    |
| Carcinogenicity:                       | Category 2                                                    |
| Reproductive toxicity:                 | Category 1B                                                   |
| GHS Label Elements                     |                                                               |
| Hazard pictograms:                     |                                                               |
|                                        |                                                               |
| Signal word:                           | Danger                                                        |
| Hazard statements:                     | Causes skin irritation.                                       |
|                                        | May cause an allergic skin reaction.                          |
|                                        | Causes serious eye irritation.                                |
|                                        | Suspected of causing cancer.                                  |
|                                        |                                                               |
|                                        | May damage fertility or the unborn child.                     |
| Precautionary statements:              |                                                               |
| Precautionary statements:              | Prevention:                                                   |
| Precautionary statements:              | <b>Prevention:</b><br>Obtain special instructions before use. |
| Precautionary statements:              | Prevention:                                                   |

Avoid breathing dust, mist, gas, vapors or spray. Wash skin and face thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear permeation resistant protective gloves and clothing. Wear eye and face protection. **Response:** IF exposed or concerned: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Storage: Store locked up. **Disposal:** Dispose of contents and container in accordance with existing federal, state, and local environmental control laws.

# 3. Composition/Information on Ingredients

#### **Hazardous Components**

| <b>Concentration</b> | Components                                       | CAS-No.         |
|----------------------|--------------------------------------------------|-----------------|
| 15 - 40%             | Epoxy Acrylate                                   | 55818-57-0      |
| 10 - 30%             | 1,1,1-trimethylol propane triacrylate            | 15625-89-5      |
| 7 - 13%              | Pentaerythritol Tetracrylate                     | 4986-89-4       |
| 5 - 10%              | Tripropylene Glycol Diacrylate                   | 42978-66-5      |
| 3 - 7%               | 1,6-Hexanedioldiacrylate                         | 13048-33-4      |
| 3 - 7%               | Acrylated Resin                                  | CAS# is a trade |
|                      |                                                  | secret          |
| 3 - 7%               | Pentaerythritol Triacrylate                      | 3524-68-3       |
| 1 - 5%               | 2-methyl-1-(4-methylthiophenyl)-2-               | 71868-10-5      |
|                      | morpholinopropan-1-one                           |                 |
| 1 - 5%               | Titanium dioxide (Rutile)                        | 13463-67-7      |
| 1 - 5%               | Bis(2,4,6-Trimethylbenzoyl)phenylphosphine oxide | 162881-26-7     |

The specific chemical identity and/or exact percentage of component(s) have been withheld as a trade secret.

# 4. First Aid Measures

#### Most Important Symptom(s)/Effect(s)

Acute: May cause allergic skin reaction with symptoms of reddening, itching, swelling, and rash., Causes skin irritation with symptoms of reddening, itching, and swelling., Causes serious eye irritation with symptoms of reddening, tearing, swelling, and burning.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops.

# Material Name: Cablelite 751-017 Blue

#### **Skin Contact**

In case of skin contact, wash affected areas with soap and water. Wash off immediately with plenty of water for at least 15 minutes. Immediately remove contaminated clothing and shoes. Call a physician if irritation develops or persists. Wash clothing and shoes before reuse.

#### Inhalation

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

#### Ingestion

If ingested, do not induce vomiting unless directed to do so by medical personnel. Call a physician immediately.

# 5. Firefighting Measures

| Suitable Extinguishing Media: | All extinguishing media are suitable. |
|-------------------------------|---------------------------------------|
|-------------------------------|---------------------------------------|

Unsuitable Extinguishing Media No Data Available

#### **Fire Fighting Procedure**

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture.

#### Hazardous Decomposition Products

By Fire and Thermal Decomposition: Carbon dioxide (CO2), carbon monoxide (CO), dense black smoke., Acrylate monomers, Aldehydes, Organic acids

#### **Unusual Fire/Explosion Hazards**

Toxic and irritating gases/fumes may be given off during burning or thermal decomposition.

# 6. Accidental Release Measures

# Spill and Leak Procedures

Cleanup personnel must use appropriate personal protective equipment. Dike or dam spilled material and control further spillage, if possible. Prevent from entering open drains and waterways. Cover spill with inert material (e. g., dry sand or earth) and collect for proper disposal.

# 7. Handling and Storage

# Handling/Storage Precautions

Avoid breathing dust, vapor, or mist. Avoid contact with skin or clothing. Avoid contact with eyes. Use only with adequate ventilation/personal protection. Wash thoroughly after handling. Keep container closed when not in use.

| Storage Temperature |               |
|---------------------|---------------|
| Minimum:            | 15 °C (59 °F) |
| Maximum:            | 30 °C (86 °F) |

# **Storage Conditions**

Inhibitor only effective in the presence of oxygen. Exposure to light may cause product polymerization.

Material Name: Cablelite 751-017 Blue

Extreme heat will result in product polymerization. Protect against heat and direct sunlight.

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### Substances to Avoid

Exothermic reaction with:, Free radical initiators, Peroxides, strong alkalis, Strong acids, Reactive metals

# 8. Exposure Controls/Personal Protection

The recommendations in this section should not be a substitute for a personal protective equipment (PPE) assessment performed by the employer as required by 29 CFR 1910 Subpart I.

#### **Exposure Limits**

#### Titanium dioxide (Rutile) (13463-67-7)

US. ACGIH Threshold Limit Values, as amended Time weighted average 10 mg/m3

- US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended Permissible exposure limit 15 mg/m3 (Total dust.)
- US. ACGIH Threshold Limit Values, as amended Hazard Designation: Group A4 Not classifiable as a human carcinogen.

Any component which is listed in section 3 and is not listed in this section does not have a known ACGIH TLV, OSHA PEL or supplier recommended occupational exposure limit.

#### Industrial Hygiene/Ventilation Measures

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate airborne concentration standards/guidelines.

#### **Respiratory Protection**

Respiratory protection is recommended in insufficiently ventilated working areas and during heating or spraying. For components with occupational exposure limits, when workers are facing concentrations above those limits, they must use appropriate certified respirators.

#### Hand Protection

Ensure gloves remain in good condition during use and replace if any deterioration is observed. Permeation resistant gloves., Nitrile rubber gloves., Avoid natural rubber gloves., Do not wear PVC gloves, as PVC absorbs acrylates.

#### **Eye Protection**

Chemical safety goggles or safety glasses with side-shields.

#### Skin Protection

Permeation resistant clothing, Gloves, long sleeved shirts and pants.

# **Additional Protective Measures**

Ultraviolet (UV) light source is used for curing this product. UV light can be hazardous to unprotected skin and eyes. Protective eyewear should always be worn when working in UV curing areas. Skin protection such as long sleeves, long pants, and gloves should be worn when UV lights are being used. Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Emergency showers and eye wash stations

Material Name: Cablelite 751-017 Blue

# 9. Physical and Chemical Properties

| State of Matter:                  | liquid                                                      |
|-----------------------------------|-------------------------------------------------------------|
| Appearance:                       | viscous liquid                                              |
| Color:                            | Blue                                                        |
| Odor:                             | characteristic                                              |
| Odor Threshold:                   | No Data Available                                           |
| pH:                               | No Data Available                                           |
| Melting Point:                    |                                                             |
| Boiling Point:                    |                                                             |
| Flash Point:                      | > 100 °C (> 212 °F) (closed cup)                            |
| Evaporation Rate:                 | No Data Available                                           |
| Lower explosion limit:            | No Data Available                                           |
| Upper Explosion Limit:            | No Data Available                                           |
| Vapor Pressure:                   | No Data Available                                           |
| Vapor Density:                    | No Data Available                                           |
| Density:                          | 1.12 g/cm <sup>3</sup> @ 20 °C (68 °F)                      |
| <b>Relative Vapor Density:</b>    | No Data Available                                           |
| Specific Gravity:                 | No Data Available                                           |
| Solubility in Water:              | No Data Available                                           |
| Partition Coefficient: n-         | No Data Available                                           |
| octanol/water:                    |                                                             |
| Auto-ignition Temperature:        | No Data Available                                           |
| <b>Decomposition Temperature:</b> | Stable under recommended storage conditions. The product is |
|                                   | chemically stable.                                          |
| Unblocking Temperature:           | No Data Available                                           |
| Dynamic Viscosity:                | 4,100 - 4,400 mPa.s @ 20 °C (68 °F)                         |
| Kinematic Viscosity:              | > 20.5 mm2/s @ 40 °C (104 °F)                               |
| Bulk Density:                     | No Data Available                                           |
| Molecular Weight:                 | No Data Available                                           |
| Self Ignition:                    | not applicable                                              |
| 5                                 | 11                                                          |

# **10. Stability and Reactivity**

#### Hazardous Reactions

No hazardous reactions when stored and handled correctly.

# Stability

Stable

#### Materials to Avoid

Exothermic reaction with:, Free radical initiators, Peroxides, strong alkalis, Strong acids, Reactive metals

#### **Conditions to Avoid**

Heat Exposure to sunlight. Protect from freezing. Product contains an inhibitor system. Must be inhibited to prevent hazardous polymerization. Inhibitor only effective in the presence of oxygen.

# **Hazardous Decomposition Products**

By Fire and Thermal Decomposition: Carbon dioxide (CO2), carbon monoxide (CO), dense black smoke., Acrylate monomers, Aldehydes, Organic acids

| Material Name: Cablelite 751-017 Blue | Material Number: 50025108 |
|---------------------------------------|---------------------------|
| Page:                                 | 5 of 18                   |

#### 11. Toxicological Information

Likely Routes of Exposure:

Skin Contact Eye Contact Ingestion Inhalation

#### **Health Effects and Symptoms**

Acute: May cause allergic skin reaction with symptoms of reddening, itching, swelling, and rash., Causes skin irritation with symptoms of reddening, itching, and swelling., Causes serious eye irritation with symptoms of reddening, tearing, swelling, and burning. Chronic: Suspected of causing cancer., May damage fertility or the unborn child.

#### Toxicity Data for: Cablelite 751-017 Blue

Data on the product is not available.

Please find the data available for the components.

Acute Oral Toxicity Acute toxicity estimate: > 5,000 mg/kg (Calculation method)

Acute Inhalation Toxicity no data available

Acute Dermal Toxicity Acute toxicity estimate: 4,753 mg/kg (Calculation method)

#### **Toxicity Data for: Epoxy Acrylate**

Acute Oral Toxicity LD50: > 2,000 mg/kg (rat, male/female) (OECD Test Guideline 401)

Acute Inhalation Toxicity LC50: > 4.9 mg/l, 4 h, dust/mist (rat, male/female) (OECD Test Guideline 403)

**Acute Dermal Toxicity** LD50: > 2,000 mg/kg (rat, male/female) (OECD Test Guideline 402)

**Skin Irritation** rabbit, OECD Test Guideline 404, non-irritant

**Eye Irritation** rabbit, OECD Test Guideline 405, slight irritant

#### Sensitization

Skin sensitization (local lymph node assay (LLNA)):: positive (Mouse, OECD Test Guideline 429)

Respiratory sensitization: No data available.

**Repeated Dose Toxicity** Oral: LOAEL: 100 mg/kg, (rat, male/female)

Material Name: Cablelite 751-017 Blue

Page: 6 of 18

#### Mutagenicity

Genetic Toxicity in Vitro: Ames test: negative (Metabolic Activation: with/without) In vitro mammalian cell gene mutation test: negative (Metabolic Activation: with/without)

Genetic Toxicity in Vivo: In vivo micronucleus test: negative (Mouse, male, Oral) negative

#### Carcinogenicity

No data available. **Toxicity to Reproduction/Fertility** Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test, Oral, (rat, male/female)

**Developmental Toxicity/Teratogenicity** rat, female, Oral, NOAEL (teratogenicity): 1000, NOAEL (maternal): > 1000 rabbit, female, Oral, NOAEL (teratogenicity): 1000, NOAEL (maternal): 1000

#### Toxicity Data for: 1,1,1-trimethylol propane triacrylate

Acute Oral Toxicity LD50: > 5,000 mg/kg (rat)

Acute Inhalation Toxicity LC50: 0.55 mg/l, 6 h, vapour (rat, male/female)

#### **Acute Dermal Toxicity**

LD50: 5,170 mg/kg (rabbit) assuming density = 1.1 g/cm3

Skin Irritation rabbit, OECD Test Guideline 404, irritating

**Eye Irritation** rabbit, Draize, irritating

#### Sensitization

Skin sensitisation:: positive (Guinea pig)

Skin sensitisation:: positive (Guinea pig)

# **Repeated Dose Toxicity**

Oral: NOAEL: 300 mg/kg, (rat, male/female, daily)

Dermal: LOAEL: 0.3 mg/kg, (rat, male/female, 5 days/week)

Dermal: NOAEL: 0.3 mg/kg, (Mouse, male/female, 5 days/week)

#### Mutagenicity

Genetic Toxicity in Vitro: Mammalian cell - gene mutation assay: positive (Mouse lymphoma cells (L5178Y/TK), Metabolic Activation: with/without) Chromosome aberration test: positive (other mammalian peripheral blood lymphocytes, Metabolic Activation: with/without)

Material Name: Cablelite 751-017 Blue

Ames test: ambiguous (Salmonella typhimurium, Metabolic Activation: with/without)

Genetic Toxicity in Vivo: Micronucleus Assay: negative (Mouse, male/female, oral) negative

# Carcinogenicity

Mouse, male, Dermal, 80, 2 times/week NOAEL: 50mg/kg body weight/day

#### **Toxicity to Reproduction/Fertility**

Oral, daily, (rat, male/female) NOAEL (parental): 300 mg/kg, NOAEL (F1): 300 mg/kg,

# **Developmental Toxicity/Teratogenicity**

rabbit, male and female, Oral, daily, NOAEL (teratogenicity): >= 130 mg/kg, NOAEL (maternal): >= 130 mg/kg,

#### Toxicity Data for: Pentaerythritol Tetracrylate

**Toxicity Note** No data available for this product.

Skin Irritation irritating

Eye Irritation irritating

# Sensitization

Skin sensitisation:: Classification according to Directive 2006/121/EC Annex VI

Respiratory sensitization: no data available

# Toxicity Data for: Tripropylene Glycol Diacrylate

Acute Oral Toxicity LD50: 6,200 mg/kg (rat)

# Acute Dermal Toxicity

LD50: > 2,000 mg/kg (rabbit, male/female) (OECD Test Guideline 402)

#### **Skin Irritation**

rabbit, OECD Test Guideline 404, negative

# Eye Irritation

rabbit, OECD Test Guideline 405, Slightly irritating

#### Sensitization

Skin sensitization (local lymph node assay (LLNA)):: positive (Mouse, OECD Test Guideline 429)

# **Repeated Dose Toxicity**

Oral: NOAEL: 375, (rat, male/female, daily)

Material Name: Cablelite 751-017 Blue

Dermal: NOAEL: 66,7, (rat, male/female, 5 days/week)

#### Mutagenicity

Genetic Toxicity in Vitro: In vitro mammalian cell gene mutation test: negative (Chinese hamster ovary (CHO) cells, Metabolic Activation: with/without) In vitro mammalian cell gene mutation test: positive (Mouse lymphoma cells, Metabolic Activation: with/without)

Genetic Toxicity in Vivo: In vivo micronucleus test: negative (Mouse, male/female, intraperitoneal) negative

In vivo micronucleus test: negative (Mouse, female, intraperitoneal) negative

#### Carcinogenicity

Mouse, male, Dermal, 2 times/week NOAEL: > 25mg/kg bw/day

#### **Toxicity to Reproduction/Fertility**

Oral, daily, (rat, male/female) Oral, daily, (rat, male/female)

#### **Developmental Toxicity/Teratogenicity**

rat, female, Oral, daily, NOAEL (maternal): > 375 rabbit, female, Oral, daily, NOAEL (maternal): 450 rat, female, Oral, daily, NOAEL (teratogenicity): 250, NOAEL (maternal): 250

#### **Other Relevant Toxicity Information**

May cause irritation of respiratory tract.

#### Toxicity Data for: 1,6-Hexanedioldiacrylate

Acute Oral Toxicity LD50: > 5,000 mg/kg (rat, male/female) (OECD Test Guideline 401)

#### **Acute Inhalation Toxicity**

LC0: 0.41 mg/l, 7 h, vapour (rat, male/female)

#### Acute Dermal Toxicity

LD50: 3,650 mg/kg (rabbit) (OECD Test Guideline 402)

#### Skin Irritation

rabbit, OECD Test Guideline 404, Exposure Time: 4 h, irritating

#### **Eye Irritation** rabbit, irritating

Sensitization Maximisation Test: positive (Guinea pig, OECD Test Guideline 406)

# Repeated Dose Toxicity

Oral: NOAEL: 250 mg/kg, (rat, male/female)

#### **Mutagenicity** Genetic Toxicity in Vitro:

Material Name: Cablelite 751-017 Blue

Ames test: negative (Metabolic Activation: with/without) In vitro mammalian cell gene mutation test: negative (Metabolic Activation: with/without)

Genetic Toxicity in Vivo: In vivo micronucleus test: negative (Mouse, Male) Studies of a comparable product. negative

#### **Toxicity to Reproduction/Fertility**

Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test, Oral, (rat, Male/Female) NOAEL (parental): 250 mg/kg,

#### **Developmental Toxicity/Teratogenicity**

rat, male and female, Oral, NOAEL (teratogenicity): 750 mg/kg, NOAEL (maternal): 250 mg/kg, Did not show teratogenic effects in animal experiments.

#### **Toxicity Data for: Acrylated Resin**

**Eye Irritation** Irritating to eyes.

#### Toxicity Data for: Pentaerythritol Triacrylate

Acute Oral Toxicity LD50: 1,830 mg/kg (rat)

Acute Dermal Toxicity LD50: 4,668 mg/kg (rabbit)

**Skin Irritation** rabbit, Moderately irritating

Draize, Moderately irritating

**Eye Irritation** rabbit, Draize, Severely irritating

# Sensitization

dermal: (Maximisation Test)

Skin sensitisation:: May cause sensitization by skin contact.

# Mutagenicity

Genetic Toxicity in Vitro: Ames: negative (Salmonella typhimurium)

Genetic Toxicity in Vivo: Micronucleus Assay: Ambiguous. (Mouse, male, dermal) Ambiguous.

# Carcinogenicity

Mouse, dermal, 80 weekspositive

# **Toxicity to Reproduction/Fertility**

Reproductive effects have been observed in animal studies. **Developmental Toxicity/Teratogenicity** 

Material Name: Cablelite 751-017 Blue

Rat, female, oral, gestation, daily, NOAEL (teratogenicity): 500 mg/kg, NOAEL (maternal): < 500 mg/kg, No Teratogenic effects observed at doses tested. Fetotoxicity seen only with maternal toxicity.

#### Toxicity Data for: 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one

# **Acute Oral Toxicity**

LD50: 1,984 mg/kg (rat, male/female) (OECD Test Guideline 401)

#### **Acute Dermal Toxicity**

LD50: > 2,000 mg/kg (rabbit, male/female) (OECD Test Guideline 402)

#### Skin Irritation

rabbit, OECD Test Guideline 404, non-irritant

#### **Eye Irritation**

rabbit, OECD Test Guideline 405, slight irritant

#### Sensitization

Skin sensitisation:: negative (Guinea pig, OECD Test Guideline 406)

Respiratory sensitization: no data available

#### **Repeated Dose Toxicity**

Oral: NOAEL: 100 mg/kg, (rat, male/female, daily)

#### Mutagenicity

Genetic Toxicity in Vitro: Ames test: negative (Salmonella typhimurium, Metabolic Activation: with/without) Chromosome aberration test in vitro: negative (Chinese hamster V79 cell line, Metabolic Activation: with/without) In vitro mammalian cell gene mutation test: negative (mouse lymphoma cells, Metabolic Activation: with/without)

Genetic Toxicity in Vivo: In vivo micronucleus test: negative (hamster, male/female, Oral) negative

# **Toxicity to Reproduction/Fertility**

Oral, daily, (rat, male/female)

**Developmental Toxicity/Teratogenicity** rat, male and female, Oral, daily, NOAEL (maternal): 40 mg/kg,

# Toxicity Data for: Titanium dioxide (Rutile)

Acute Oral Toxicity LD50: > 5,000 mg/kg (rat, female) (OECD Test Guideline 425)

Acute Inhalation Toxicity LC50: > 6.82 mg/l, 4 h, dust/mist (rat, male)

# Acute Dermal Toxicity

LD50:>10,000 mg/kg (rabbit)

Material Name: Cablelite 751-017 Blue

#### Skin Irritation

rabbit, OECD Test Guideline 404, Exposure Time: 24 h, Non-irritating

rabbit, Exposure Time: 24 h, Non-irritating

#### **Eye Irritation** rabbit, OECD Test Guideline 405, Non-irritating

rabbit, Draize, Non-irritating

#### Sensitization

dermal: non-sensitizer (Guinea pig, Maximization Test)

dermal: non-sensitizer (Human, Patch Test)

Skin sensitization (local lymph node assay (LLNA)):: negative (Mouse, OECD Test Guideline 429)

dermal: non-sensitizer (Guinea pig, Maximization Test)

dermal: non-sensitizer (Human, Patch Test)

#### **Repeated Dose Toxicity**

28 Days, inhalation: NOAEL: 35 mg/m3, (Rat)

29 days, Oral: NOAEL: 24,000 mg/kg, (rat, male, daily)

up to 2 years, inhalation: NOAEL: 0.01 mg/l, (Rat, male/female, 6 hrs/day 5 days/week)

28 Days, inhalation: NOAEL: 35 mg/m3, (Rat)

#### Mutagenicity

Genetic Toxicity in Vitro: Ames: negative (Salmonella typhimurium, Metabolic Activation: with/without) Mammalian cell - gene mutation assay: negative (Mouse lymphoma cells (L5178Y/TK), Metabolic Activation: with/without) Chromosome aberration test: negative (Chinese hamster ovary (CHO) cells, Metabolic Activation: with/without) Ames: negative (Salmonella typhimurium, Metabolic Activation: with/without)

Genetic Toxicity in Vivo: Drosophila SLRL test: negative (Drosophila melanogaster) negative

Cytogenetic assay: negative (Mouse, male, intraperitoneal) negative

Drosophila SLRL test: negative (Drosophila melanogaster) negative

#### Carcinogenicity

Rat, Male/Female, inhalationAccording to IARC, several rat inhalation and intratracheal installation studies using titanium dioxide have shown increases in benign and malignant lung tumors. Reviewed human exposure data did not suggest an association between occupational exposure to titanium dioxide and risk for cancer. Additionally, the IARC working group determined that, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other material, such as in paints."Rat, Male/Female, inhalationAccording to IARC, several rat inhalation and intratracheal

| Material Name: Cablelite 751-017 Blue | Material Number: 50025108 |
|---------------------------------------|---------------------------|
| Page: 1                               | 12 of 18                  |

installation studies using titanium dioxide have shown increases in benign and malignant lung tumors. Reviewed human exposure data did not suggest an association between occupational exposure to titanium dioxide and risk for cancer. Additionally, the IARC working group determined that, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other material, such as in paints."

#### **Other Relevant Toxicity Information**

May cause irritation of respiratory tract.

# Toxicity Data for: Bis(2,4,6-Trimethylbenzoyl)phenylphosphine oxide

Acute Oral Toxicity LD50: > 2,000 mg/kg (rat)

Acute Dermal Toxicity LD50: > 2,000 mg/kg (rat)

**Skin Irritation** Non-irritating

**Eye Irritation** rabbit, non-irritant

**Sensitization** dermal: sensitizer (Guinea pig)

#### **Repeated Dose Toxicity**

28 days, Oral: NOAEL: 1,000 mg/kg, (rat) There were no adverse effects seen at highest dose tested.

**Mutagenicity** Genetic Toxicity in Vitro: Ames: Negative results were reported in various in vitro studies.

# Carcinogenicity:

| 1,1,1-trimethylol propane<br>triacrylate | IARC - Overall evaluation: 2B Possibly carcinogenic to humans. |
|------------------------------------------|----------------------------------------------------------------|
| Titanium dioxide (Rutile)                | IARC - Overall evaluation: 2B Possibly carcinogenic to humans. |

# **12. Ecological Information**

#### Ecological Data for: Cablelite 751-017 Blue

No data available for this product. Please find below the data available to us for the hazardous components:

#### **Ecological Data for Epoxy Acrylate**

#### Biodegradation

42 %, Exposure time: 28 d, i.e. not readily degradable

#### Bioaccumulation

An accumulation in aquatic organisms is not to be expected.

#### Acute and Prolonged Toxicity to Fish

Material Name: Cablelite 751-017 Blue

LC50: > 0.082 mg/l (Cyprinus carpio (Carp), 96 h) No toxic effects in the water-soluble range.

# Acute Toxicity to Aquatic Invertebrates

EL50: > 100 mg/l (Daphnia magna (Water flea), 48 h)

**Toxicity to Aquatic Plants** EL50: 105 mg/l, (Pseudokirchneriella subcapitata (green algae), 72 h)

**Toxicity to Microorganisms** EC50: > 1,000 mg/l, (activated sludge, 3 h)

Ecological Data for 1,1,1-trimethylol propane triacrylate Biodegradation aerobic, 82 - 90 %, Exposure time: 28 d, i.e. readily biodegradable

**Bioaccumulation** 123 BCF Accumulation in aquatic organisms is unlikely.

Acute and Prolonged Toxicity to Fish LC50: 0.87 mg/l (Danio rerio (zebra fish), 96 h)

Acute Toxicity to Aquatic Invertebrates LC50: 19.9 mg/l (Daphnia magna (Water flea), 48 h)

#### **Toxicity to Aquatic Plants** EC50: 18.8 mg/l, (Desmodesmus subspicatus (Green algae), 72 h)

ErC50: 4.86 mg/l, (scenedesmus subspicatus, 72 h)

EC50: 18.8 mg/l, (Desmodesmus subspicatus (Green algae), 72 h)

EC10: 1.9 mg/l, (Desmodesmus subspicatus (Green algae), 72 h)

# Toxicity to Microorganisms

EC20: 625 mg/l, (activated sludge, 0.5 h)

# Ecological Data for Pentaerythritol Tetracrylate

Additional Ecotoxicological Remarks No data available for this product.

Ecological Data for Tripropylene Glycol Diacrylate Biodegradation

40 - 50 %, i.e. not readily degradable

# Bioaccumulation

Accumulation in aquatic organisms is unlikely.

Acute and Prolonged Toxicity to Fish

LC50: 1 - 10 mg/l (Leuciscus idus (Golden orfe), 96 h)

Acute Toxicity to Aquatic Invertebrates EC50: 10 - 100 mg/l (Daphnia magna (Water flea), 48 h)

# **Toxicity to Aquatic Plants**

Material Name: Cablelite 751-017 Blue

ErC50: 10 - 100 mg/l, (scenedesmus subspicatus, 72 h)

**Toxicity to Microorganisms** EC50: > 10,000 mg/l, (Pseudomonas putida, 0.5 h)

# Ecological Data for 1,6-Hexanedioldiacrylate

**Biodegradation** 60 - 70 %, Exposure time: 28 d, i.e. inherently degradable

60 - 70 %, Exposure time: 28 d, i.e. readily biodegradable

# Acute and Prolonged Toxicity to Fish

LC50: 0.38 mg/l (Oryzias latipes (Japanese medaka), 96 h)

# Acute Toxicity to Aquatic Invertebrates

EC50: 2.7 mg/l (Daphnia magna (Water flea), 48 h)

#### **Toxicity to Aquatic Plants**

EC50: 2.33 mg/l, (Selenastrum capricornutum (green algae), 72 h)

NOEC: 0.9 mg/l, (Selenastrum capricornutum (green algae), 72 h)

# Toxicity to Microorganisms

EC50: 270 mg/l, (activated sludge, 30 min)

# Ecological Data for Pentaerythritol Triacrylate

**Biodegradation** 6 - 14 %, Exposure time: 28 d, i.e. not readily degradable

# Acute and Prolonged Toxicity to Fish

LC50: 3.2 mg/l (Cyprinus carpio (Carp), 96 h)

NOEC: 2.2 mg/l (Cyprinus carpio (Carp), 96 h)

# Acute Toxicity to Aquatic Invertebrates

EC50: 13 mg/l (Daphnia magna (Water flea), 48 h)

NOEC: 10.3 mg/l (Daphnia magna (Water flea), 48 h)

# **Toxicity to Aquatic Plants**

ErC50: 12 mg/l, End Point: Growth inhibition (Pseudokirchneriella subcapitata (green algae), 96 h)

#### Ecological Data for 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one Biodegradation

aerobic, <= 1 %, Exposure time: 28 d, i.e. not readily degradable

# Bioaccumulation

Oryzias latipes (Orange-red killifish), Exposure time: 56 d, < 10 BCF

# Acute and Prolonged Toxicity to Fish

LC50: 9 mg/l (Danio rerio (zebra fish), 96 h)

# Acute Toxicity to Aquatic Invertebrates

EC50: 15.3 mg/l (Daphnia magna (Water flea), 24 h)

# **Toxicity to Aquatic Plants**

Material Name: Cablelite 751-017 Blue

EC50: 1.6 mg/l, (Desmodesmus subspicatus (Green algae), 72 h)

NOEC: 0.86 mg/l, (Desmodesmus subspicatus (Green algae), 72 h)

**Toxicity to Microorganisms** EC50: > 100 mg/l, (activated sludge, 3 h)

# Ecological Data for Titanium dioxide (Rutile)

Acute and Prolonged Toxicity to Fish LC0: > 1,000 mg/l (Golden orfe (Leuciscus idus), 48 h)

Acute Toxicity to Aquatic Invertebrates EC0: > 3 mg/l (Water flea (Daphnia magna))

**Toxicity to Microorganisms** 

EC0: > 10,000 mg/l, (Pseudomonas fluorescens, 24 h)

# Ecological Data for Bis(2,4,6-Trimethylbenzoyl)phenylphosphine oxide

**Biodegradation** Exposure time: 28 d, Not readily biodegradable.

# Bioaccumulation

Cyprinus carpio (Carp), < 5 BCF

# Acute and Prolonged Toxicity to Fish

LC50: > 90 ppm (Zebra fish (Brachydanio rerio), 96 h) No harmful effect at saturation concentration.

# Acute Toxicity to Aquatic Invertebrates

EC50: > 1.175 mg/l (Water flea (Daphnia magna), 48 h) No effects seen at saturation concentration.

# **Toxicity to Aquatic Plants**

EC50: 0.26 mg/l, (Green algae (Scenedesmus subspicatus), 72 h) No effects seen at saturation concentration.

# **Toxicity to Microorganisms**

EC50: > 100 mg/l, (Wastewater bacteria)

# **13. Disposal Considerations**

# Waste Disposal Method

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

# **Empty Container Precautions**

Do not reuse empty container. Empty containers retain product residue (dust, liquid, vapor and/or gases) and can be dangerous.

# **14. Transportation Information**

#### Land transport (DOT) Non-Regulated

Material Name: Cablelite 751-017 Blue

| <u>Sea transport (IMDG)</u>                                                          |                                                                                                                        |
|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Proper Shipping Name:                                                                | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,                                                                           |
|                                                                                      | N.O.S. (contains BADGE epoxy acrylate, Trimethylolpropane                                                              |
|                                                                                      | triacrylate)                                                                                                           |
| Hazard Class or Division:                                                            | 9                                                                                                                      |
| UN number:                                                                           | UN3082                                                                                                                 |
| Packaging Group:                                                                     | III                                                                                                                    |
| Hazard Label(s):                                                                     | MISCELLANEOUS                                                                                                          |
| Marine pollutant:                                                                    | Marine pollutant                                                                                                       |
|                                                                                      |                                                                                                                        |
|                                                                                      |                                                                                                                        |
| <u>Air transport (ICAO/IATA)</u>                                                     |                                                                                                                        |
| <u>Air transport (ICAO/IATA)</u><br>Proper Shipping Name:                            | Environmentally hazardous substance, liquid, n.o.s. (contains                                                          |
| • • • •                                                                              | Environmentally hazardous substance, liquid, n.o.s. (contains<br>BADGE epoxy acrylate, Trimethylolpropane triacrylate) |
| • • • •                                                                              |                                                                                                                        |
| Proper Shipping Name:                                                                | BADGE epoxy acrylate, Trimethylolpropane triacrylate)                                                                  |
| Proper Shipping Name:<br>Hazard Class or Division:                                   | BADGE epoxy acrylate, Trimethylolpropane triacrylate)<br>9                                                             |
| Proper Shipping Name:<br>Hazard Class or Division:<br>UN number:                     | BADGE epoxy acrylate, Trimethylolpropane triacrylate)<br>9<br>UN3082                                                   |
| Proper Shipping Name:<br>Hazard Class or Division:<br>UN number:<br>Packaging Group: | BADGE epoxy acrylate, Trimethylolpropane triacrylate)<br>9<br>UN3082<br>III                                            |

# **15. Regulatory Information**

#### **United States Federal Regulations**

US. Toxic Substances Control Act: Listed on the Active Portion of the TSCA Inventory.

No substances are subject to TSCA 12(b) export notification requirements.

#### US. EPA CERCLA Hazardous Substances (40 CFR 302.4) Components:

C.I. Pigment Blue 15

Included in the regulation but with no data values. See regulation for further details

# SARA Section 311/312 Hazard Categories:

Refer to hazard classification information in Section 2.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components: None

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required Components: None

# US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

# State Right-To-Know Information

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

| Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists: |                |  |  |            |                           |
|--------------------------------------------------------------------------|----------------|--|--|------------|---------------------------|
| <b>Concentration</b>                                                     | Components     |  |  | CAS-No.    |                           |
| 15 - 40%                                                                 | Epoxy Acrylate |  |  | 55818-57-0 |                           |
| Material Name: Cablelite                                                 | 751-017 Blue   |  |  |            | Material Number: 50025108 |
| Page: 17 of 18                                                           |                |  |  |            |                           |

| 10 - 30% | 1,1,1-trimethylol propane triacrylate                        | 15625-89-5             |
|----------|--------------------------------------------------------------|------------------------|
| >=1%     | Aliphatic urethane acrylate                                  | CAS# is a trade secret |
| 7 - 13%  | Pentaerythritol Tetracrylate                                 | 4986-89-4              |
| 5 - 10%  | Tripropylene Glycol Diacrylate                               | 42978-66-5             |
| 3 - 7%   | 1,6-Hexanedioldiacrylate                                     | 13048-33-4             |
| 3 - 7%   | Acrylated Resin                                              | CAS# is a trade secret |
| 3 - 7%   | Pentaerythritol Triacrylate                                  | 3524-68-3              |
| 1 - 5%   | 2-Benzoyl-2-hydroxypropane                                   | 7473-98-5              |
| 1 - 5%   | 2-methyl-1-(4-methylthiophenyl)-2-<br>morpholinopropan-1-one | 71868-10-5             |
| 1 - 5%   | Titanium dioxide (Rutile)                                    | 13463-67-7             |
| 1 - 5%   | Bis(2,4,6-                                                   | 162881-26-7            |
|          | Trimethylbenzoyl)phenylphosphine                             |                        |
|          | oxide                                                        |                        |

#### California Proposition 65 List:

| <b>Concentration</b> | <b>Components</b>                     | CAS-No.    |
|----------------------|---------------------------------------|------------|
| 10 - 30%             | 1,1,1-trimethylol propane triacrylate | 15625-89-5 |
| 1 - 5%               | Titanium dioxide (Rutile)             | 13463-67-7 |
| <100 ppm             | Toluene                               | 108-88-3   |

#### CFATS (Chemical Facility Anti-Terrorism Standards) Chemicals

To the best of our knowledge, this product does not contain Appendix A Chemicals of Interest (COI), at or above the Screening Threshold Quantity (STQ), as defined by the Department of Homeland Security Chemical Facility Anti-terrorism Standard (CFATS, 6 CFR Part 27).

Based on information provided by our suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716; File No. S7-40-10; Date: 2012-08-22).

# 16. Other Information

The method of hazard communication for Covestro LLC is comprised of product labels and safety data sheets. Safety data sheets for all of our products and general product declarations are available for download at www.productsafetyfirst.covestro.com.

| Contact:      | Product Safety Department |
|---------------|---------------------------|
| Telephone:    | (412) 413-2835            |
| Version Date: | 12/05/2023                |
| SDS Version:  | 1.5                       |

Information contained in this Safety Data Sheet (SDS) is believed to be accurate but is furnished without warranty, express or implied, including warranties of merchantability or fitness for a particular purpose. The information relates only to the specific material designated herein. Covestro LLC assumes no legal responsibility for use of or reliance upon the information in this SDS and such information shall in no case be considered a part of our terms and conditions of sale. The user is responsible for determining whether the Covestro product is suitable for user's method of use or application. Covestro is not liable for any failure to observe the precautionary measures described in this SDS or for any misuse of the product.

Material Name: Cablelite 751-017 Blue