

### **Manufacturer:**

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

#### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)



Safety Data Sheet

A Meridian Adhesives Group Company

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/18/2022 Revision date: 5/22/2023 Supersedes: 5/18/2022 Version: 2.0

#### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture

: EPO-TEK® 301 PART B

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives Recommended use : Adhesives

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

#### 1.3. Supplier

Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA 01821

USA

T 978-667-3805 - F 978-663-9782

www.epotek.com

#### 1.4. Emergency telephone number

: VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585 Emergency number

#### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### GHS US classification

Acute toxicity (oral) Category 4 H302 Harmful if swallowed

H314 Skin corrosion/irritation Category 1A Causes severe skin burns and eve damage Serious eve damage/eye irritation Category 1 H318 Causes serious eve damage Skin sensitization, Category 1 H317 May cause an allergic skin reaction Hazardous to the aquatic environment - Chronic Hazard Category 3 Harmful to aquatic life with long lasting effects H412

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling

Hazard pictograms (GHS US)

Precautionary statements (GHS US)





Signal word (GHS US)

: H302 - Harmful if swallowed Hazard statements (GHS US)

H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H412 - Harmful to aquatic life with long lasting effects : P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing must not be allowed out of the workplace.

Data is subject to change without notice.





#### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

#### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **EPO-TEK® 301 PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P330 - Rinse mouth.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Trimethyl-1, 6-Hexanediamine	CAS-No.: 25513-64-8		Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Comments

: Components not listed are either non-hazardous or are below reportable limits

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

: Call a physician immediately.

First-aid measures after inhalation First-aid measures after skin contact : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after eye contact

: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.

 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion

: Rinse mouth. Do not induce vomiting. Call a physician immediately.

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

#### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4q)

### **EPO-TEK® 301 PART B**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact Symptoms/effects after eye contact

: Burns, May cause an allergic skin reaction.

: Serious damage to eyes.

Symptoms/effects after ingestion

: Burns.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information Dispose of materials or solid residues at an authorized site

### 6.4. Reference to other sections

For further information refer to section 13

### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **EPO-TEK® 301 PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **EPO-TEK® 301 PART B**

No additional information available

Trimethyl-1, 6-Hexanediamine (25513-64-8)

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):







#### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Color clear Odor : Amine-like Odor threshold : No data available : No data available pΗ Melting point : No data available Freezing point : No data available No data available Boiling point Flash point : No data available

 ${\it Data is subject to change without notice}.$ 





### **Manufacturer:**

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET301-4G

Cliel, hove for more data

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

#### **EPO-TEK® 301 PART B**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1) : No data available Flammability : Not applicable. Vapor pressure : No data available Relative vapor density at 20°C No data available : No data available Relative density Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available

#### 9.2. Other information

No additional information available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

### EPO-TEK® 301 PART B

ATE US (oral) 910 mg/kg body weight

#### Trimethyl-1, 6-Hexanediamine (25513-64-8)

LD50 oral rat 910 mg/kg body weight Animal: rat, Animal sex: male

ATE US (oral) 910 mg/kg body weight

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

#### **EPO-TEK® 301 PART B**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation : Causes severe skin burns.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified

Trimethyl-1, 6-Hexanediamine (25513-64-8)

LOAEL (oral,rat,90 days) 60 mg/kg body weight Animal: rat

NOAEL (oral,rat,90 days) 10 mg/kg body weight Animal: rat

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions

#### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

DOT NA No : UN2327 UN-No. (TDG) : UN2327 UN-No. (IMDG) : 2327 UN-No. (IATA) : 2327

 ${\it Data is subject to change without notice}.$ 





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

Trimethylhexamethylenediamines (TRIMETHYLHEXAMETHYLENEDIAMINES)

### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **EPO-TEK® 301 PART B**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Trimethylhexamethylenediamines (TRIMETHYLHEXAMETHYLENEDIAMINES)

Proper Shipping Name (TDG) : TRIMETHYLHEXAMETHYLENEDIAMINES (TRIMETHYLHEXAMETHYLENEDIAMINES)

Proper Shipping Name (IMDG) : TRIMETHYLHEXAMETHYLENEDIAMINES (TRIMETHYLHEXAMETHYLENEDIAMINES)

#### 14.3. Transport hazard class(es)

Proper Shipping Name (IATA)

DOT

Transport hazard class(es) (DOT) : Hazard labels (DOT) :



TDG

Transport hazard class(es) (TDG) :
Hazard labels (TDG) :



IMDG

Transport hazard class(es) (IMDG) : Hazard labels (IMDG) :



IATA

Transport hazard class(es) (IATA) :
Hazard labels (IATA) :



#### 14.4. Packing group

 Packing group (DOT)
 : III

 Packing group (TDG)
 : III

 Packing group (IMDG)
 : III

 Packing group (IATA)
 : III

### 14.5. Environmental hazards

Other information : No supplementary information available

#### 14.6. Special precautions for user

DOT UN-No.(DOT) : UN2327

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4q)

### **EPO-TEK® 301 PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal... ..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241 DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

: 60 L

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

UN-No. (TDG) : UN2327 Explosive Limit and Limited Quantity Index : 5 L Excepted quantities (TDG) : E1 Passenger Carrying Road Vehicle or Passenger : 5 L Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 153

Limited quantities (IMDG) : 5L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : P001, LP01 IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T4 Tank special provisions (IMDG) : TP1

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG)

Properties and observations (IMDG) : Colourless, slightly hygroscopic, combustible liquids. Miscible with water. Irritating to skin, eyes

and mucous membranes.

IATA

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y841 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 852 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 856 CAO max net quantity (IATA) : 60L Special provision (IATA) A803 ERG code (IATA) : 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET301-4G

Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (4g)

### **EPO-TEK® 301 PART B**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### 15.2. International regulations

CANADA

#### Trimethyl-1, 6-Hexanediamine (25513-64-8)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### National regulations

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

#### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date

Full text of H-phrases		
H302	Harmful if swallowed	
H314	Causes severe skin burns and eye damage	
H317	May cause an allergic skin reaction	
H318	Causes serious eye damage	
H412	Harmful to aquatic life with long lasting effects	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

Data is subject to change without notice.

